




# 4453 STEPLIGHT

## Fluorescent & Incandescent Recessed



### Specifications

|    |                     |
|----|---------------------|
| L: | 10 - 1/4"<br>260 mm |
| W: | 3 - 7/8"<br>99 mm   |
| H: | 3 - 3/4"<br>96 mm   |

IP66

|                |  |
|----------------|--|
| CATALOG NUMBER |  |
| NOTES          |  |
| TYPE           |  |

### DESCRIPTION

Hydrel's 4453 compact recessed step and wall light is a rugged fixture designed for concrete, block, or brick applications with limited space. These heavy wall cast aluminum or bronze lights are completely weatherproof; sealed with silicone gasket, tempered lens, and stainless steel fasteners.

### ORDERING INFORMATION

EXAMPLE: 4453 A 13DTT 120 LLV LPI BZ

| 4453    | A                            | 13DTT  |  |
|---------|------------------------------|--|--|
| Model   | Material                     | Lamp Type  |  |
| 4453    | A Aluminum<br>B Bronze       | <b>INCANDESCENT<sup>1</sup></b><br>40I T-10 40W Med.<br><b>FLUORESCENT</b><br>7TT 2G7 4 PIN<br>9TT 2G7 4 PIN<br>13DTT G24Q-1 4 PIN |  |
| 120     | LLV                          | LPI  | BZ   |
| Voltage | Accessories                  | Lamp   | Finish <sup>3</sup>                        |
| 120     | <b>External</b>              | LPI Lamp Included  | BL Black                                   |
| 277     | LLV <sup>2</sup> Louver Door |  | BZ Bronze                                  |
| 347     |                              |  | DDB Dark Bronze                            |
|         |                              |  | DNA Natural Aluminum                       |
|         |                              |  | GN Green                                   |
|         |                              |  | GR Gray                                    |
|         |                              |  | SND Sand                                   |
|         |                              |  | STG Steel Gray                             |
|         |                              |  | TVG Terra Verde Green                      |
|         |                              |  | WH White                                   |
|         |                              |  | CF Custom                                  |
|         |                              |  | __Z <sup>4</sup> Zinc Undercoat (i.e. BLZ) |

### FEATURES & SPECIFICATIONS

- MATERIAL:** Cast aluminum or cast bronze.
- LAMP:** Incandescent: 40 Watt Max., T-10 lamp  
Fluorescent: 13 Watt Max., CFL Twin Tube or Double Twin Tube.
- SOCKET:** Incandescent: Medium screw base  
Fluorescent: 4-Pin base
- BALLAST:** Fluorescent: Electronic ballast high frequency with -18°C (0°F) minimum starting temperature.
- VOLTAGE:** See ordering guide for options.
- REFLECTOR:** Flat polished stainless steel.
- LENS:** Diffused, tempered glass for non-louvered door. Clear, tempered glass for louvered door.
- CONDUIT ENTRIES:** 3/4" NPT side entries standard.
- ACCESSORIES:** LLV - Louver door, 45° cut-off.
- FINISH:** Super durable Polyester TGIC powder coat finish (standard). Optional Zinc undercoat for harsh environments.
- FASTENERS:** Stainless steel.
- LISTING:** U.L., CSA

#### Notes:

- 1 Incandescent models available in 120 Volt only.
- 2 LLV Louver Door available with clear lens only.
- 3 Finish is natural aluminum or bronze unless finish specified.
- 4 Add Zinc undercoat for harsh environments.

**NOTE:** Hydrel Reserves The Right To Modify Specification Without Notice. Any dimension on this sheet is to be assumed as a reference dimension: "Used for information purposes only. It does not govern manufacturing or inspection requirements." (ANSI Y14.5-1973)



9144 Deering Avenue, Second Floor • Chatsworth, CA 91311 • www.hydrel.com  
Phone: 866.533.9901 • Fax: 866.533.5291

©2014 Acuity Brands Lighting, Inc.  
6/18/14  
4453