



4456 STEPLIGHT

HID Fluorescent & Incandescent Recessed



Specifications

L:	13" 330 mm
W:	6 - 1/2" 165 mm
H:	6" 153 mm

IP66

4456 LLV Louver Door
Accessory shown

CATALOG
NUMBER

NOTES

TYPE

DESCRIPTION

Hydrel's 4456 recessed step and wall light is a rugged fixture designed for concrete, block, or brick applications. These heavy wall cast aluminum lights are completely weatherproof; sealed with louvered door, silicone gasket, tempered lens, and stainless steel fasteners. The 4456 operates incandescent, compact fluorescent, and High Intensity Discharge lamps. Emergency egress fluorescent fixture with battery back-up also available.

ORDERING INFORMATION

EXAMPLE: 4456 50M 120 LLV ELN LPI

Model	Lamp Type	Voltage	Accessories
4456	INCANDESCENT¹	120 277 347 ⁴ MVOLT ⁴	External LLV Louver Door
	75I A-19 Med. Base		
	FLUORESCENT		
	18TRT GX24Q-2 4PIN		
	26TRT GX24Q-3 4PIN		
	32TRT GX24Q-3 4PIN		
	42TRT GX24Q-4 4PIN		
	MH		
	50M E17 Med. Base		
	HPS¹		
	50S E17 Med. Base		

Options ⁵	Lamp	Finish ²
Emergency	LPI Lamp Included	BL Black
ELN⁴ Nickel Cadmium Battery Backup		BZ Bronze
SF³ Single Fuse		DDB Dark Bronze
		DNA Natural Aluminum
		GN Green
		GR Gray
		SND Sand
		STG Steel Gray
		TVG Terra Verde Green
		WH White
		CF Custom
		_Z⁶ Zinc Undercoat (i.e. BLZ)

FEATURES & SPECIFICATIONS

MATERIAL: Cast aluminum.

LAMP: Incandescent: 75 Watt Max., A19 lamp
Fluorescent: 42 Watt Max., CFL Twin Tube
HID: 50 Watt Max., E17 Lamp.

SOCKET: Incandescent: Medium screw base
Fluorescent: 4-Pin base
HID: Medium screw base, pulse rated

BALLAST: Fluorescent: Electronic ballast high frequency with -18°C (0°F) minimum starting temperature.
HID: Magnetic ballast high power factor with -30°C (-20°F) minimum starting temperature.

VOLTAGE: See ordering guide for options.

REFLECTOR: Flat polished stainless steel. Fluorescent: white finish.

LENS: Diffused, tempered glass for non-louvered door. Clear, tempered glass for louvered door.

CONDUIT ENTRIES: 3/4" NPT side entries standard.

ACCESSORIES: LLV - Louver door, 45° cut-off.
ELN - Nickel Cadmium Battery Backup.

FINISH: Super durable Polyester TGIC powder coat finish (standard). Optional Zinc undercoat for harsh environments.

FASTENERS: Stainless steel.

LISTING: U.L., CSA

WARRANTY: 5-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Notes:

- Available in 120 Volt only.
- Finish is natural aluminum unless finish specified.
- SF only available with MH and HPS lamps.
- Only valid with 18TRT, 26TRT, 32TRT & 42TRT.
- Specify voltage 120 or 277.
- Add Zinc undercoat for harsh environments.



9144 Deering Avenue, Second Floor • Chatsworth, CA 91311
Phone: 866.533.9901 • www.hydel.com

©2014-2017 Acuity Brands Lighting, Inc.
11/02/17
4456