

INSTALLATION INSTRUCTIONS

MACB/MFS9450

Installation should be performed by a qualified electrician in accordance with the National Electrical Code and relevant local codes.

NOTICE:

DO NOT CONNECT LAMP MODULE WHILE SYSTEM IS ENERGIZED. TURN OFF POWER PRIOR TO LAMPING.

CAUTION: Temporary cover must remain in housing until ready to connect power module/cord.

1. Remove temporary cover from rough-in section.
2. Install MFS9450 (finish-in section) into top of rough-in housing. **DO NOT SECURE RING TO HOUSING.**
3. Plug power module/cord into base of MACB (lamp module assembly). **PUSH** cord end directly into module base, **DO NOT TWIST.**
4. Place lamp module assembly into MFS (finish section) in rough-in housing. Position module into ring by aligning lamp module and MFS securement holes.
5. Energize the fixture, allowing it to fully reach operating temperature and light output.
Caution: Avoid looking directly into light source during aiming. Fixture lens may become hot. Avoid contact with bare skin.
6. Rotate the lamp module and its support ring until desired position is achieved.
7. Once the desired aiming position is determined, secure the MFS ring into the housing with the attached fasteners.
Caution: DO NOT OVER TIGHTEN (20 in-lbs or 2 N-m).
8. Secure MACB (lamp module) to MFS support ring with the fasteners provided.
Caution: DO NOT OVER TIGHTEN (20 in-lbs or 2 N-m).

INSTALLATION DIAGRAM

